

Project: Snake Valley
 Date Logged: 24-Sep-08
 Well: UGS PW01C
 Owner: Utah Geological Survey
 Location: (C-21-20)36ccc
 UTM.E: 235724 UTM.N: 4314668
 Water Level: 137.05 M 449.6 FT

DEPTH (M)	KOHM	R	LN®	T(K)	T(°C)	T(°F)
10	129.44	191.1661	5.253142451	0.003502	12.40	54.32
20	127.90	187.8191	5.235479322	0.003498	12.75	54.95
30	127.79	187.5815	5.234213376	0.003497	12.78	55.00
40	128.35	188.7932	5.240652182	0.003499	12.65	54.77
45	128.48	189.0752	5.242144775	0.003499	12.62	54.72
50	128.52	189.1620	5.242603873	0.003499	12.61	54.70
55	128.68	189.5096	5.244439514	0.003500	12.57	54.63
60	128.74	189.6400	5.245127569	0.003500	12.56	54.61
65	128.79	189.7487	5.245700819	0.003500	12.55	54.59
70	128.79	189.7487	5.245700819	0.003500	12.55	54.59
75	128.78	189.7270	5.245586179	0.003500	12.55	54.59
80	128.72	189.5965	5.244898236	0.003500	12.56	54.62
85	128.61	189.3575	5.24363657	0.003500	12.59	54.66
90	128.50	189.1186	5.242374333	0.003499	12.61	54.71
95	128.33	188.7498	5.240422481	0.003499	12.65	54.78
100	128.27	188.6198	5.239733266	0.003499	12.67	54.80
105	128.13	188.3166	5.238124432	0.003498	12.70	54.86
110	127.92	187.8623	5.235709432	0.003498	12.75	54.95
115	127.73	187.4520	5.233522616	0.003497	12.79	55.02
120	127.52	186.9991	5.231103593	0.003497	12.84	55.11
125	127.29	186.5038	5.228451746	0.003496	12.89	55.20
130	127.05	185.9879	5.225681868	0.003495	12.95	55.30
135	126.75	185.3444	5.222215572	0.003494	13.02	55.43
140	126.47	184.7450	5.21897638	0.003494	13.08	55.54
145	126.17	184.1041	5.215501523	0.003493	13.15	55.67
150	125.85	183.4221	5.21179008	0.003492	13.22	55.80
155	125.52	182.7204	5.207957287	0.003491	13.30	55.94
160	125.17	181.9781	5.203886206	0.003490	13.38	56.08
165	124.85	181.3010	5.20015863	0.003489	13.45	56.22
170	124.47	180.4990	5.195725329	0.003488	13.54	56.38
175	124.10	179.7203	5.191401536	0.003487	13.63	56.53
180	123.74	178.9646	5.18718777	0.003486	13.71	56.68
185	123.34	178.1272	5.182497838	0.003485	13.81	56.85
190	122.96	177.3339	5.178034566	0.003484	13.90	57.01
195	122.55	176.4805	5.173210292	0.003483	13.99	57.19
200	122.15	175.6503	5.168494967	0.003481	14.09	57.36
205	121.74	174.8018	5.163652743	0.003480	14.18	57.53
210	121.33	173.9558	5.15880131	0.003479	14.28	57.71
215	120.86	172.9891	5.153228475	0.003478	14.39	57.91
220	120.55	172.3532	5.149546031	0.003477	14.47	58.04
225	120.15	171.5349	5.144786499	0.003476	14.56	58.21
230	119.74	170.6985	5.139898558	0.003475	14.66	58.39

DEPTH (M)	KOHM	R	LN ®	T(K)	T(°C)	T(°F)
235	119.34	169.8848	5.135120561	0.003473	14.76	58.56
240	118.94	169.0735	5.130333323	0.003472	14.85	58.73
245	118.50	168.1837	5.12505659	0.003471	14.96	58.93
250	118.05	167.2765	5.119648149	0.003470	15.07	59.12
255	117.63	166.4324	5.114589417	0.003468	15.17	59.30
260	117.20	165.5709	5.109399277	0.003467	15.27	59.49
265	116.78	164.7319	5.104319031	0.003466	15.38	59.68
270	116.42	164.0147	5.099955958	0.003465	15.46	59.84
275	115.97	163.1208	5.094490883	0.003464	15.57	60.03
280	115.56	162.3088	5.089500627	0.003462	15.68	60.22
285	115.18	161.5583	5.08486609	0.003461	15.77	60.38
290	114.87	160.9475	5.081078515	0.003460	15.85	60.52
295	114.37	159.9652	5.074956596	0.003459	15.97	60.75
300	113.94	159.1232	5.069678864	0.003458	16.08	60.94
305	113.51	158.2837	5.064389098	0.003456	16.18	61.13
310	113.12	157.5245	5.059580901	0.003455	16.28	61.31
315	112.73	156.7673	5.054762623	0.003454	16.38	61.48
320	112.32	155.9735	5.049686289	0.003453	16.48	61.67
325	111.92	155.2013	5.044722839	0.003451	16.58	61.85
330	111.51	154.4119	5.039623998	0.003450	16.69	62.03
335	111.13	153.6824	5.034887935	0.003449	16.78	62.21
340	110.75	152.9547	5.030141867	0.003448	16.88	62.38
345	110.38	152.2480	5.025511002	0.003447	16.97	62.55
350	109.99	151.5051	5.020619378	0.003446	17.07	62.73
355	109.61	150.7832	5.015842782	0.003444	17.17	62.91
360	109.23	150.0631	5.011055836	0.003443	17.27	63.08
365	108.86	149.3638	5.006384832	0.003442	17.36	63.25
370	108.47	148.6286	5.001450536	0.003441	17.46	63.43
375	108.09	147.9141	4.996632003	0.003440	17.56	63.61
380	107.72	147.2203	4.991929982	0.003439	17.66	63.78
385	107.33	146.4908	4.986962711	0.003437	17.76	63.97
390	106.97	145.8192	4.982367354	0.003436	17.85	64.14
395	106.58	145.0934	4.977377921	0.003435	17.96	64.32
400	106.28	144.5365	4.973531958	0.003434	18.03	64.46
405	105.90	143.8326	4.968650415	0.003433	18.13	64.64
410	105.55	143.1860	4.964144302	0.003432	18.23	64.81
415	105.19	142.5224	4.959499401	0.003431	18.32	64.98
420	104.81	141.8238	4.95458531	0.003430	18.42	65.16
425	104.46	141.1819	4.950048969	0.003429	18.52	65.33
430	104.11	140.5415	4.94550276	0.003427	18.61	65.50
435	103.75	139.8844	4.940816283	0.003426	18.71	65.67
440	103.37	139.1925	4.935857933	0.003425	18.81	65.86
445	103.00	138.5205	4.931018609	0.003424	18.91	66.03
450	102.63	137.8502	4.926167882	0.003423	19.01	66.21
455	102.29	137.2358	4.92170032	0.003422	19.10	66.38
460	101.91	136.5506	4.916695577	0.003421	19.20	66.57
465	101.57	135.9391	4.912207198	0.003419	19.30	66.73
470	101.20	135.2752	4.907311475	0.003418	19.40	66.91
475	100.86	134.6666	4.902802225	0.003417	19.49	67.08
480	100.54	134.0951	4.898548985	0.003416	19.58	67.24

DEPTH (M)	KOHM	R	LN ®	T(K)	T(°C)	T(°F)
485	100.14	133.3823	4.893219729	0.003415	19.69	67.44
490	99.96	133.0622	4.890816926	0.003414	19.74	67.53

